



IMS Person Management Services WSDL Binding

Version 1.0 Final Specification

IPR and Distribution Notices

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the specification set forth in this document, and to provide supporting documentation.

IMS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on IMS's procedures with respect to rights in IMS specifications can be found at the IMS Intellectual Property Rights web page: http://www.imsglobal.org/ipr/imsipr_policyFinal.pdf.

Copyright © 2004 IMS Global Learning Consortium. All Rights Reserved.

If you wish to copy or distribute this document, you must complete a valid Registered User license registration with IMS and receive an email from IMS granting the license to distribute the specification. To register, follow the instructions on the IMS website: <http://www.imsglobal.org/specificationdownload.cfm>.

This document may be copied and furnished to others by Registered Users who have registered on the IMS website provided that the above copyright notice and this paragraph are included on all such copies. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to IMS, except as needed for the purpose of developing IMS specifications, under the auspices of a chartered IMS project group.

Use of this specification to develop products or services is governed by the license with IMS found on the IMS website: <http://www.imsglobal.org/license.html>.

The limited permissions granted above are perpetual and will not be revoked by IMS or its successors or assigns.

THIS SPECIFICATION IS BEING OFFERED WITHOUT ANY WARRANTY WHATSOEVER, AND IN PARTICULAR, ANY WARRANTY OF NONINFRINGEMENT IS EXPRESSLY DISCLAIMED. ANY USE OF THIS SPECIFICATION SHALL BE MADE ENTIRELY AT THE IMPLEMENTER'S OWN RISK, AND NEITHER THE CONSORTIUM, NOR ANY OF ITS MEMBERS OR SUBMITTERS, SHALL HAVE ANY LIABILITY WHATSOEVER TO ANY IMPLEMENTER OR THIRD PARTY FOR ANY DAMAGES OF ANY NATURE WHATSOEVER, DIRECTLY OR INDIRECTLY, ARISING FROM THE USE OF THIS SPECIFICATION.

Copyright © 2004 by IMS Global Learning Consortium, Inc.
All Rights Reserved.

The IMS Logo is a registered trademark of IMS Global Learning Consortium, Inc.

Document Name: IMS Person Management Services WSDL Binding

Date: 11 June 2004

Table of Contents

1.	INTRODUCTION	5
1.1	PERSON MANAGEMENT SERVICES OVERVIEW	5
1.2	SCOPE AND CONTEXT	5
1.3	STRUCTURE OF THIS DOCUMENT	6
1.4	NOMENCLATURE	6
1.5	REFERENCES	6
2.	APPLICATION OF THE WSDL BINDING GUIDELINES	8
2.1	SYNCHRONOUS BINDING	8
2.2	ASYNCHRONOUS BINDING	9
3.	DATA MODEL XML SCHEMAS BINDING	10
3.1	<PERSON> ELEMENT	10
3.2	<FORMATNAME> ELEMENT	10
3.3	<NAME> ELEMENT	10
3.4	<RECORDINFO> ELEMENT	11
3.5	<EMAIL> ELEMENT	11
3.6	<URL> ELEMENT	11
3.7	<SYSTEMROLE> ELEMENT	11
3.8	<USERID> ELEMENT	11
3.9	<ADDRESS> ELEMENT	11
3.10	<DEMOGRAPHICS> ELEMENT	12
3.11	<INSTITUTIONROLE> ELEMENT	12
3.12	<TEL> ELEMENT	12
3.13	<PHOTO> ELEMENT	13
3.14	<DATASOURCE> ELEMENT	13
3.15	<EXTENSION> ELEMENT	13
3.16	<PERSONSET> ELEMENT	13
3.17	<PERSONIDPAIR> ELEMENT	13
3.18	<PERSONIDPAIRSET> ELEMENT	14
3.19	<SOURCEDIDSET> ELEMENT	14
3.20	<PAIRSOURCEDIDSET> ELEMENT	14
4.	SYNCHRONOUS WSDL BINDING	15
4.1	SOAP SPECIFIC SERVICE BINDING	15
4.2	ABSTRACT DEFINITION BINDING	15
4.3	MESSAGE XML SCHEMAS	15
4.3.1	<i>'createPersonRequest' Message</i>	<i>15</i>
4.3.2	<i>'createPersonResponse' Message</i>	<i>15</i>
4.3.3	<i>'createByProxyPersonRequest' Message</i>	<i>16</i>
4.3.4	<i>'createByProxyPersonResponse' Message</i>	<i>16</i>
4.3.5	<i>'deletePersonRequest' Message</i>	<i>16</i>
4.3.6	<i>'deletePersonResponse' Message</i>	<i>17</i>
4.3.7	<i>'readPersonRequest' Message</i>	<i>17</i>
4.3.8	<i>'readPersonResponse' Message</i>	<i>17</i>
4.3.9	<i>'updatePersonRequest' Message</i>	<i>17</i>
4.3.10	<i>'updatePersonResponse' Message</i>	<i>18</i>
4.3.11	<i>'replacePersonRequest' Message</i>	<i>18</i>
4.3.12	<i>'replacePersonResponse' Message</i>	<i>18</i>
4.3.13	<i>'changePersonIdentifierRequest' Message</i>	<i>18</i>

4.3.14 ‘changePersonIdentifierResponse’ Message19

4.3.15 ‘createPersonsRequest’ Message.....19

4.3.16 ‘createPersonsResponse’ Message19

4.3.17 ‘createByProxyPersonsRequest’ Message.....20

4.3.18 ‘createByProxyPersonsResponse’ Message20

4.3.19 ‘deletePersonsRequest’ Message20

4.3.20 ‘deletePersonsResponse’ Message.....20

4.3.21 ‘readPersonsRequest’ Message21

4.3.22 ‘readPersonsResponse’ Message.....21

4.3.23 ‘readPersonsForGroupRequest’ Message.....21

4.3.24 ‘readPersonsForGroupResponse’ Message21

4.3.25 ‘updatePersonsRequest’ Message.....22

4.3.26 ‘updatePersonsResponse’ Message22

4.3.27 ‘replacePersonsRequest’ Message.....22

4.3.28 ‘replacePersonsResponse’ Message23

4.3.29 ‘changePersonIdentifierRequest’ Message23

4.3.30 ‘changePersonIdentifierResponse’ Message.....23

4.4 EXAMPLE SOAP/HTTP MESSAGES23

5. ASYNCHRONOUS WSDL BINDING25

APPENDIX A – BINDING WSDL LISTINGS26

A1 – SYNCHRONOUS BINDING.....26

ABOUT THIS DOCUMENT27

LIST OF CONTRIBUTORS27

REVISION HISTORY28

INDEX.....29

1. Introduction

1.1 Person Management Services Overview

The Person Management Services specification [PersonServices, 04] is the definition of how systems manage the exchange of information that describes people within the context of learning. The Person Management Services specification is constructed following the recommendations documented in the IMS Abstract Framework (IAF) [AbsGloss, 03], [AbsASC, 03], [AbsWhite, 03]. This means that this specification is based upon the concepts of:

- Interoperability – Person Management Services focuses on the exchange of Person(s) information between Enterprise systems. There are no assumptions in the specification on how the data is managed within the Enterprise systems;
- Service-oriented – Person Management Services defines the exchange of information in terms of the services being supplied by the collaboration of the systems;
- Component-based – the Person Management Services will be combined with the Group Management Services and Membership Management Services to provide the Enterprise Service. Other services will be added to it in later releases;
- Layering – the Person Management Service is a part of the Application Services layer but it interacts with the services available in the Common Services layer, e.g., authentication;
- Behaviors and Data Models – the Person Management Services are defined in terms of their behaviors and data models. The behaviors cause changes in the state of the data model and the state of the data model will only be altered as a result of a clearly defined behavior;
- Multiple Bindings – the Person Management Services information model is to be defined using the Unified Modelling Language (UML). This enables reliable mapping of the information model into a range of different bindings. The bindings of immediate importance are to the Web Services Description Language (WSDL);
- Adoption – the Person Management Services are based upon the original Enterprise specification data model. While there are significant changes the underlying data model has been maintained and the core Person structures remain.

1.2 Scope and Context

This document is the IMS Person Management Services WSDL Binding v1.0 and as such it is used in conjunction with the following documents:

- a) IMS Enterprise Services Core Use Cases v1.0 [EntServices, 04a] – the set of use cases that are the basis for the definition of the Person Management Services Information Model;
- b) IMS Person Management Services Information Model v1.0 [PersonServices, 04] – the behavior and data model definition of the Person Management Services;
- c) IMS Enterprise Services Best Practice & Implementation Guide v1.0 [EntServices, 04c] – this presents information that helps implementers adopt the specification;
- d) IMS Enterprise Services Conformance Specification v1.0 [EntServices, 04b] – the definition of the conformance criteria that must be followed by systems that wish to claim compliance to the Enterprise Services Information Model.

As such the Person Management Services specification supersedes the original Enterprise specifications:

- a) IMS Enterprise Information Model Final Specification v1.1 [Enterprise, 02a].
- b) IMS Enterprise XML Binding Final Specification v1.1 [Enterprise, 02b];
- c) IMS Enterprise Services Best Practice & Implementation Guide Final Specification v1.1 [Enterprise, 02c].

This WSDL binding takes the Person Management Service Information Model and produces an encoding of that description in WSDL. This WSDL binding is generated as recommended by the IMS General Web Services documents [GWS, 04a], [GWS, 04b].

1.3 Structure of this Document

The structure of this document is:

- | | |
|---|--|
| 2. Application of the WSDL Binding Guidelines | A description of how the General Web Services WSDL binding guidelines have been applied to the Person Management Services Information Model; |
| 3. Data Model Binding | The description of the XML schemas that are created to reflect the data model of the Person Management Services Information Model; |
| 4. Synchronous WSDL Binding | The description of the SOAP messages and the corresponding XML schemas that are created as the synchronous WSDL binding; |
| 5. Asynchronous WSDL Binding | The description of the SOAP messages and the corresponding XML schemas that are created as the asynchronous WSDL binding; |
| Appendix A – Binding Files Listings | The WSDL listings for the synchronous and asynchronous SOAP/http binding of the Person Management Services Information Model. |

1.4 Nomenclature

API	Application Programming Interface
IAF	IMS Abstract Framework
UML	Unified Modelling Language
W3C	World Wide Web Consortium
WSDL	Web Services Description Language
XML	Extensible Mark-up Language

1.5 References

- | | |
|--------------------|---|
| [AbsASCs, 03] | <i>IMS Abstract Framework: Applications, Services & Components v1.0</i> , Ed. C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2003. |
| [AbsGloss, 03] | <i>IMS Abstract Framework: Glossary v1.0</i> , Ed. C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2003. |
| [AbsWhite, 03] | <i>IMS Abstract Framework: White Paper v1.0</i> , Ed. C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2003. |
| [Cockburn, 01] | <i>Writing Effective Use-case</i> , A.Cockburn, <u>Addison-Wesley</u> , 2001, ISBN 0-201-70225-8. |
| [CommonData, 04] | <i>IMS Enterprise Services Common Data Definitions Specification v1.0</i> , C.Smythe and C.Vento, <u>IMS Global Learning Consortium, Inc.</u> , June 2004. |
| [Enterprise, 02a] | <i>IMS Enterprise Information Model v1.1</i> , G.Collier, C.Etesse, W.Veris and C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2002. |
| [Enterprise, 02b] | <i>IMS Enterprise XML Binding v1.1</i> , G.Collier, C.Etesse, W.Veris and C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2002. |
| [Enterprise, 02c] | <i>IMS Enterprise Best Practice & Implementation Guide v1.1</i> , G.Collier, C.Etesse, W.Veris and C.Smythe, <u>IMS Global Learning Consortium, Inc.</u> , July 2002. |
| [EntServices, 04a] | <i>IMS Enterprise Services Core Use Cases Description v1.0</i> , C.Smythe and C.Vento, <u>IMS Global Learning Consortium, Inc.</u> , June 2004. |
| [EntServices, 04b] | <i>IMS Enterprise Services Conformance Specification v1.0</i> , C.Smythe and C.Vento, <u>IMS Global Learning Consortium, Inc.</u> , June 2004. |

- [EntServices, 04c] *IMS Enterprise Services Best Practices & Implementation Guide v1.0*, C.Smythe and C.Vento, IMS Global Learning Consortium, Inc., June 2004.
- [GWS, 04a] *IMS General Web Services Base Profiles v1.0*, C.Schroeder, S.Raju, and C.Smythe, IMS Global Learning Consortium, Inc., June 2004.
- [GWS, 04b] *IMS General Web Services Binding Methodology & Recipes v1.0*, C.Schroeder, S.Raju, and C.Smythe, IMS Global Learning Consortium, Inc., June 2004.
- [PersonServices, 04] *IMS Person Management Services Information Model v1.0*, C.Smythe and C.Vento, IMS Global Learning Consortium, Inc., June 2004.
- [SpecDev, 03] *IMS Specification Development Methods & Best Practices Draft 5.0*, C.Smythe, IMS Global Learning Consortium, Inc., August 2003.

2. Application of the WSDL Binding Guidelines

2.1 Synchronous Binding

The WSDL bindings have been generated using the methodology documented in [GWS 04a] and [GWS, 04b]. The composition of the synchronous WSDL binding is shown in Figure 2.1.




Figure 2.1 Person WSDL and XSD synchronous binding file composition.

The binding files described in Figure 2.1 contain:

- ‘imsPersonManServiceSyncv1p0.wsdl’ – the service specific WSDL binding file. For the Person Management Service this is based upon SOAP/http. This file imports the abstract definitions using the <wSDL:import> construct. The listing of this file is given in Appendix A;
- ‘imsPersonManAbstractSyncv1p0.wsdl’ – the abstract message definitions that represent the behavior of the Person Management Service operations. This file imports the message XSD using the <xsd:import> construct. The listing of this file is given in Appendix A;
- ‘imsPersonManMessSchemav1p0.xsd’ – the XSD definitions for the synchronous and asynchronous messages. This file imports the Person data model XSD using the <xsd:import> construct. The listing of this file is given in Appendix A;
- ‘imsPersonManDataSchemav1p0.xsd’ – the definition of the Person data model. This is the file that was produced by the equivalent data model binding in Enterprise v1.1. The listing of this file is given in Appendix A;

- ‘imsMessBindSchemav1p0.xsd’ – the XSD binding of the message header parts. This includes the message headers for synchronous, polled and asynchronous message models;
- ‘imsCommonSchemav1p0.xsd’ – the XSD binding of the IMS Enterprise Service common data objects. This file is used by the Person message and data model XSDs as well as the IMS message binding XSD;
- ‘wsiwsdlv1p1.xsd’ – this is the reference XSD for the WSDL definition. This file is the WS-I amended version of the original file from W3C;
- ‘wsisoapv1p1.xsd’ – this is the reference XSD for the SOAP extensions to WSDL. This file is from WS-I.

The name spaces and prefixes used within these bindings are listed in Table 2.1.

Table 2.1 The namespaces used in the synchronous binding files.

Namespace	Prefix	Usage
–	“tns:”	The target namespace identifier.
http://www.w3.org/2001/XMLSchema	“xsd:”	The XML schema definition namespace.
/imsCommonSchemav1p0	“esx:”	The IMS Enterprise Service common data model definitions namespace.
/imsMessBindSchemav1p0	“isb:”	The IMS message header binding definitions namespace.
/pms/xsd/imsPersonManDataSchemav1p0	“per:”	The data model namespace for the Person class.
/pms/xsd/imsPersonManMessSchemav1p0	“impsms:”	The IMS Person Management Services message binding definitions namespace.
/pms/wSDL/imsPersonManAbstractSyncv1p0	“absp:”	The Person Management Service abstract definitions file references.
wsisoapv1p1	“soap:”	The SOAP references used within the WSDL files.
wsiwsdlv1p1	“wSDL:”	The default WSDL files namespace for WSDL v1.1.

2.2 Asynchronous Binding

Note: At the time of publication the Asynchronous Binding had not been tested. The details for creating the Asynchronous Binding are available in the IMS Person Management Service WSDL Binding V2.0 Public Draft document. The Asynchronous Binding details will be issued in V2.0 of this document once testing has been completed.

3. Data Model XML Schemas Binding

3.1 <person> Element

The XSD visualization of the <person> data model is shown in Figure 3.1. This is the XML equivalent of the UML description in Figure 4.1 and Table 4.1 [PersonServices, 04].




Figure 3.1 <person> element composition.

3.2 <formatName> Element

See Table 4.1 and the OCL definitions in sub-section 4.1.4 [PersonServices, 04].

3.3 <name> Element

The XSD visualization of the <name> data model is shown in Figure 3.2. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1, 4.3, 4.4 and 4.5 [PersonServices, 04].




Figure 3.2 <name> element composition.

3.4 <recordInfo> Element

The XSD visualization of the <recordInfo> data model is shown in Figure 3.3. This is the XML equivalent of the UML description in Figure 4.1 and Table 4.1 [PersonServices, 04a].




Figure 3.3 <recordInfo> element composition.

3.5 <email> Element

See Table 4.1 and the OCL definitions in sub-section 4.1.4 [PersonServices, 04].

3.6 <URL> Element

See Table 4.1 and the OCL definitions in sub-section 4.1.4 [PersonServices, 04].

3.7 <systemRole> Element

See Table 4.1 and the OCL definitions in sub-section 4.1.4 [PersonServices, 04].

3.8 <userId> Element

The XSD visualization of the <userId> data model is shown in Figure 3.4. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 [PersonServices, 04].




Figure 3.4 <userId> element composition.

3.9 <address> Element

The XSD visualization of the <address> data model is shown in Figure 3.5. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 and 4.7 [PersonServices, 04].




Figure 3.5 <address> element composition.

3.10 <demographics> Element

The XSD visualization of the <demographics> data model is shown in Figure 3.6. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 and 4.6 [PersonServices, 04].




Figure 3.6 <demographics> element composition.

3.11 <institutionRole> Element

The XSD visualization of the <institutionRole> data model is shown in Figure 3.7. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 and 4.9 [PersonServices, 04].




Figure 3.7 <institutionRole> element composition.

3.12 <tel> Element

The XSD visualization of the <tel> data model is shown in Figure 3.8. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 and 4.8 [PersonServices, 04].




Figure 3.8 <tel> element composition.

3.13 <photo> Element

The XSD visualization of the <photo> data model is shown in Figure 3.9. This is the XML equivalent of the UML description in Figure 4.1 and Tables 4.1 and 4.10 [PersonServices, 04].




Figure 3.9 <photo> element composition.

3.14 <dataSource> Element

See Table 4.1 and the OCL definitions in sub-section 4.1.4 [PersonServices, 04].

3.15 <extension> Element

The XSD visualization of the <extension> data model is shown in Figure 3.10. This is the XML equivalent of the UML description in Figure 4.1 and Table 4.1 [PersonServices, 04].




Figure 3.10 <extension> element composition.

3.16 <personSet> Element

The XSD visualization of the <personSet> data model is shown in Figure 3.11. This is the XML equivalent of the UML description in Figure 4.2 and Table 4.11 [PersonServices, 04a].




Figure 3.11 <personSet> element composition.

3.17 <personIdPair> Element

The XSD visualization of the <personIdPair> data model is shown in Figure 3.12. This is the XML equivalent of the UML description in Figure 4.3 and Table 4.13 [PersonServices, 04].



Figure 3.12 <personIdPair> element composition.

3.18 <personIdPairSet> Element

The XSD visualization of the <personIdPairSet> data model is shown in Figure 3.13. This is the XML equivalent of the UML description in Figure 4.3 and Table 4.12 [PersonServices, 04].




Figure 3.13 <personIdPairSet> element composition.

3.19 <sourcedIdSet> Element

The XSD visualization of the <sourcedIdSet> data model is shown in Figure 3.14.




Figure 3.14 <sourcedIdSet> element composition.

3.20 <pairSourcedIdSet> Element

The XSD visualization of the <pairSourcedIdSet> data model is shown in Figure 3.15. This is the XML equivalent of the UML description in Figure 4.2 [CommonData, 04].



Figure 3.15 <pairSourcedIdSet> element composition.

4. Synchronous WSDL Binding

4.1 SOAP Specific Service Binding

The key properties of the Specific Service binding files are detailed in Table 4.1. The Service Specific filename is: 'imsPersonManServiceSyncv1p0.wsdl'.

Table 4.1 Properties of the specific service file.

Property	Value
Transport Mechanism	SOAPv1.1/HTTPv1.1
Service Name	"PersonManagementServiceSync"
Service Port Name	"PersonManagementServiceSyncSoap"
Service Binding Name	"PersonManagementServiceSyncSoap"
Binding Port Type	"PersonManagementServiceSync"

4.2 Abstract Definition Binding

The key properties of the Specific Service binding files are detailed in Table 4.2. The Abstract Definitions filename is: 'imsPersonManAbstractSyncv1p0.wsdl'.

Table 4.2 Properties of the abstract definitions file.

Property	Value
Port Type Name	"PersonManagementServiceSync"

4.3 Message XML Schemas

4.3.1 'createPersonRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'createPerson()' operation. See 'createPerson()' sub-section of [PersonServices, 04].




Figure 4.1 <createPersonRequest> element composition.

Two parameters are supplied:

- sourcedId – the unique identifier to be assigned to the new Person record;
- person – the Person data to be stored in the new record.

4.3.2 'createPersonResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'createPerson()' operation. See 'createPerson()' sub-section of [PersonServices, 04].



Figure 4.2 <createPersonResponse> element composition.

The <createPersonResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.3 ‘createByProxyPersonRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘createByProxyPerson()’ operation. See ‘createByProxyPerson()’ sub-section of [PersonServices, 04].



Figure 4.3 <createByProxyPersonRequest> element composition.

One parameter is supplied:

- person – the Person data to be stored in the new record.

4.3.4 ‘createByProxyPersonResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘createByProxyPerson()’ operation. See ‘createByProxyPerson()’ sub-section of [PersonServices, 04].




Figure 4.4 <createByProxyPersonResponse> element composition.

The returned information is:

- sourcedId – the unique identifier assigned by the Sync Agent to the new record.

Note: The status information is returned in the header of the SOAP transport message.

4.3.5 ‘deletePersonRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘deletePerson()’ operation. See ‘deletePerson()’ sub-section of [PersonServices, 04].



Figure 4.5 <deletePersonRequest> element composition.

One parameter is supplied:

- sourcedId – the identifier of the Person record to be deleted;

4.3.6 'deletePersonResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'deletePerson()' operation. See 'deletePerson()' sub-section of [PersonServices, 04].



Figure 4.6 <deletePersonResponse> element composition.

The <deletePersonResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.7 'readPersonRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'readPerson()' operation. See 'readPerson()' sub-section of [PersonServices, 04].



Figure 4.7 <readPersonRequest> element composition.

One parameter is supplied:

- sourcedId – the identifier of the Person record to be read.

4.3.8 'readPersonResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'readPerson()' operation. See 'readPerson()' sub-section of [PersonServices, 04].



Figure 4.8 <readPersonResponse> element composition.

The returned information is:

- person – the returned person record.

Note: The status information is returned in the header of the SOAP transport message.

4.3.9 'updatePersonRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'updatePerson()' operation. See 'updatePerson()' sub-section of [PersonServices, 04].



Figure 4.9 <updatePersonRequest> element composition.

Two parameters are supplied:

- sourcedId – the identifier of the Person record to be changed;
- person – the Person data to be stored in the new record.

4.3.10 ‘updatePersonResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘updatePerson()’ operation. See ‘updatePerson()’ sub-section of [PersonServices, 04].



Figure 4.10 <updatePersonResponse> element composition.

The <updatePersonResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.11 ‘replacePersonRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘replacePerson()’ operation. See ‘replacePerson()’ sub-section of [PersonServices, 04].



Figure 4.11 <replacePersonRequest> element composition.

Two parameters are supplied:

- sourcedId – the identifier of the Person record to be changed;
- person – the Person data to be stored in the new record.

4.3.12 ‘replacePersonResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘replacePerson()’ operation. See ‘replacePerson()’ sub-section of [PersonServices, 04].



Figure 4.12 <replacePersonResponse> element composition.

The <replacePersonResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.13 ‘changePersonIdentifierRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘changePersonIdentifier()’ operation. See ‘changePersonIdentifier()’ sub-section of [PersonServices, 04].




Figure 4.13 <changePersonIdentifierRequest> element composition.

Two parameters are supplied:

- sourcedId – the identifier of the Person whose identifier is to be changed;
- newSourcedId – the new identifier for the Person record.

4.3.14 ‘changePersonIdentifierResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘changePersonIdentifier()’ operation. See ‘changePersonIdentifier()’ sub-section of [PersonServices, 04].



Figure 4.14 <changePersonIdentifierResponse> element composition.

The <changePersonIdentifierResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.15 ‘createPersonsRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘createPersons()’ operation. See ‘createPersons()’ sub-section of [PersonServices, 04].



Figure 4.15 <createPersonsRequest> element composition.

One parameter is supplied:

- personIdPairSet – the list of identifier and person tuples for the new Person records.

4.3.16 ‘createPersonsResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘createPersons()’ operation. See ‘createPersons()’ sub-section of [PersonServices, 04a].



Figure 4.16 <createPersonsResponse> element composition.

The <createPersonsResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.17 'createByProxyPersonsRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'createByProxyPersons()' operation. See 'createByProxyPersons()' sub-section of [PersonServices, 04].



Figure 4.17 <createByProxyPersonsRequest> element composition.

One parameter is supplied:

- personSet – the set of Person records to be created.

4.3.18 'createByProxyPersonsResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'createByProxyPersons()' operation. See 'createByProxyPersons()' sub-section of [PersonServices, 04].



Figure 4.18 <createByProxyPersonsResponse> element composition.

The returned information is:

- sourcedIdSet – the set of unique identifiers that have been allocated by the Sync Agent to the newly created records.

Note: The status information is returned in the header of the SOAP transport message.

4.3.19 'deletePersonsRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'deletePersons()' operation. See 'deletePersons()' sub-section of [PersonServices, 04a].



Figure 4.19 <deletePersonsRequest> element composition.

One parameter is supplied:

- sourcedIdSet – the set of unique identifiers for the Person records that are to be deleted.

4.3.20 'deletePersonsResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'deletePersons()' operation. See 'deletePersons()' sub-section of [PersonServices, 04].



Figure 4.20 <deletePersonsResponse> element composition.

The <deletePersonsResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.21 'readPersonsRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'readPersons()' operation. See 'readPersons()' sub-section of [PersonServices, 04].




Figure 4.21 <readPersonsRequest> element composition.

One parameter is supplied:

- sourcedIdSet – the set of unique identifiers for the Person records that are to be read.

4.3.22 'readPersonsResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'readPersons()' operation. See 'readPersons()' sub-section of [PersonServices, 04].



Figure 4.22 <readPersonsResponse> element composition.

The returned information is:

- personSet – the set of Person records that have been read.

Note: The status information is returned in the header of the SOAP transport message.

4.3.23 'readPersonsForGroupRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'readPersonsForGroup()' operation. See 'readPersonsForGroup()' sub-section of [PersonServices, 04a].



Figure 4.23 <readPersonsForGroupRequest> element composition.

One parameter is supplied:

- groupSourcedIdSet – the identifier of the Group whose Person members records are to be returned.

4.3.24 'readPersonsForGroupResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'readPersonsForGroup()' operation. See 'readPersonsForGroup()' sub-section of [PersonServices, 04].



Figure 4.24 <readPersonsForGroupResponse> element composition.

The returned information is:

- personSet – the set of Person records that have been read.

Note: The status information is returned in the header of the SOAP transport message.

4.3.25 ‘updatePersonsRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘updatePersons()’ operation. See ‘updatePersons()’ sub-section of [PersonServices, 04].




Figure 4.25 <updatePersonsRequest> element composition.

One parameter is supplied:

- personIdPairSet – the list of identifier and person tuples for the Person records to be changed.

4.3.26 ‘updatePersonsResponse’ Message

This is the response message from the Sync Agent to the Reference Agent to complete the ‘updatePersons()’ operation. See ‘updatePersons()’ sub-section of [PersonServices, 04].



Figure 4.26 <updatePersonsResponse> element composition.

The <updatePersonsResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.27 ‘replacePersonsRequest’ Message

This is the request message from the Reference Agent to the Sync Agent to invoke the ‘updatePersons()’ operation. See ‘updatePersons()’ sub-section of [PersonServices, 04].



Figure 4.27 <replacePersonsRequest> element composition.

One parameter is supplied:

- personIdPairSet – the list of identifier and person tuples for the Person records to be changed.

4.3.28 'replacePersonsResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'replacePersons()' operation. See 'replacePersons()' sub-section of [PersonServices, 04].



Figure 4.28 <replacePersonsResponse> element composition.

The <replacePersonsResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.3.29 'changePersonsIdentifierRequest' Message

This is the request message from the Reference Agent to the Sync Agent to invoke the 'changePersonsIdentifier()' operation. See 'changePersonsIdentifier()' sub-section of [PersonServices, 04].



Figure 4.29 <changePersonsIdentifierRequest> element composition.

One parameter is supplied:

- pairSourcedIdSet – the list of paired old and new identifier.

4.3.30 'changePersonsIdentifierResponse' Message

This is the response message from the Sync Agent to the Reference Agent to complete the 'changePersonsIdentifier()' operation. See 'changePersonsIdentifier()' sub-section of [PersonServices, 04].



Figure 4.30 <changePersonsIdentifierResponse> element composition.

The <changePersonsIdentifierResponse> element is empty.

Note: The status information is returned in the header of the SOAP transport message.

4.4 Example SOAP/HTTP Messages

The set of example SOAP/HTTP messages are described in Table 4.3.

Table 4.3 SOAP/HTTP example messages for the synchronous binding.

Message	Example File
'createPersonRequest' Message	/examples/createPersonRequestSync.txt
'createPersonResponse' Message	/examples/createPersonResponseSync.txt
'createByProxyPersonRequest' Message	/examples/createByProxyPersonRequestSync.txt
'createByProxyPersonResponse' Message	/examples/createByProxyPersonResponseSync.txt
'deletePersonRequest' Message	/examples/deletePersonRequestSync.txt
'deletePersonResponse' Message	/examples/deletePersonResponseSync.txt
'readPersonRequest' Message	/examples/readPersonRequestSync.txt
'readPersonResponse' Message	/examples/readPersonResponseSync.txt
'updatePersonRequest' Message	/examples/updatePersonRequestSync.txt
'updatePersonResponse' Message	/examples/updatePersonResponseSync.txt
'replacePersonRequest' Message	/examples/replacePersonRequestSync.txt
'replacePersonResponse' Message	/examples/replacePersonResponseSync.txt
'changePersonIdentifierRequest' Message	/examples/changePersonIdentifierRequestSync.txt
'changePersonIdentifierResponse' Message	/examples/changePersonIdentifierResponseSync.txt
'createPersonsRequest' Message	/examples/createPersonsRequestSync.txt
'createPersonsResponse' Message	/examples/createPersonsResponseSync.txt
'createByProxyPersonsRequest' Message	/examples/createByProxyPersonsRequestSync.txt
'createByProxyPersonsResponse' Message	/examples/createByProxyPersonsResponseSync.txt
'deletePersonsRequest' Message	/examples/deletePersonsRequestSync.txt
'deletePersonsResponse' Message	/examples/deletePersonsResponseSync.txt
'readPersonsRequest' Message	/examples/readPersonsRequestSync.txt
'readPersonsResponse' Message	/examples/readPersonsResponseSync.txt
'readPersonsForGroupRequest' Message	/examples/readPersonsForGroupRequestSync.txt
'readPersonsForGroupResponse' Message	/examples/readPersonsForGroupResponseSync.txt
'updatePersonsRequest' Message	/examples/updatePersonsRequestSync.txt
'updatePersonsResponse' Message	/examples/updatePersonsResponseSync.txt
'replacePersonsRequest' Message	/examples/replacePersonsRequestSync.txt
'replacePersonsResponse' Message	/examples/replacePersonsResponseSync.txt
'changePersonsIdentifierRequest' Message	/examples/changePersonsIdentifierRequestSync.txt
'changePersonsIdentifierResponse' Message	/examples/changePersonsIdentifierResponseSync.txt

5. Asynchronous WSDL Binding

Note: At the time of publication the Asynchronous Binding had not been tested. The details for creating the Asynchronous Binding are available in the IMS Person Management Service WSDL Binding V2.0 Public Draft document. The Asynchronous Binding details will be issued in V2.0 of this document once testing has been completed.

Appendix A – Binding WSDL Listings

A1 – Synchronous Binding

The bindings listed below are for the synchronous SOAPv1.1/HTTPv1.1 based implementation. The set of binding files are given in Table A.1. These files can be accessed by ‘clicking’ on the appropriate file name.

Table A.1 List of synchronous binding files.

Property	Value
Service Specific File	/pms/wsdl/imsPersonManServiceSync_v1p0.wsdl
Abstract Definitions File	/pms/wsdl/imsPersonManAbstractSync_v1p0.wsdl
Messages XSD	/pms/xsd/imsPersonManMessSchema_v1p0.xsd
Data Model XSD	/pms/xsd/imsPersonManDataSchema_v1p0.xsd
Enterprise Common XSD	/services/common/imsCommonSchema_v1p0.xsd
Message Binding XSD	/services/common/imsMessBindSchema_v1p0.xsd

A2 – Asynchronous Binding

Note: At the time of publication the Asynchronous Binding had not been tested. The details for creating the Asynchronous Binding are available in the IMS Person Management Service WSDL Binding V2.0 Public Draft document. The Asynchronous Binding details will be issued in V2.0 of this document once testing has been completed.

About This Document

Title	IMS Person Management Services WSDL Binding
Editor	Colin Smythe (IMS)
Team Co-Lead	Chris Vento (WebCT Inc.)
Version	1.0
Version Date	11 June 2004
Status	Final Specification
Summary	This document presents the IMS Person Management Services WSDL Binding. The original Enterprise specification was based upon the description of the data model for the information to be exchanged between communicating enterprise systems. The Enterprise Services specification extends this work by adding a series of behavioural models that define how the data models are to be manipulated. The material in this document describes the Web Services Description Language binding of the Person Management Services Information Model using SOAPv1.1/HTTPv1.1 as the underlying messaging and transport mechanism. This version supersedes the IMS Enterprise v1.1 specifications.
Revision Information	11 June 2004
Purpose	This document has been approved by the IMS Technical Board and is made available for adoption.
Document Location	http://www.imsglobal.org/es/esv1p0/imsperson_bindv1p0.html

To register any comments or questions about this specification please visit:
<http://www.imsglobal.org/developers/ims/imsforum/categories.cfm?catid=20>

List of Contributors

The following individuals contributed to the development of this document:

Name	Organization	Name	Organization
Scott Baker	Oracle Inc.	Les Smith	SCT Inc.
Fred Beshears	UC Berkeley, USA	Colin Smythe	Dunelm Services Ltd.
Kerry Blinco	IMS Australia	Chris Vento	WebCT Inc.
Chris Etesse	Blackboard Inc.	Kimberley Voltero	WebCT Inc.
John Hallet	WebCT Inc.	Scott Wilson	JISC (CETIS), UK
Cathy Schroeder	Microsoft Inc.	Nathaniel Zinn	Blackboard Inc.

Revision History

Version No.	Release Date	Comments
Public Draft 1.0	12 January 2004	The final approved Public Draft Document for the IMS Person Management Services Specification.
Public Draft 2.0	19 April 2004	This is the second formal release of the Public Draft Document for the IMS Person Management Services Specification. The differences to the first release are: a) The asynchronous binding information has been added; b) In the synchronous binding Section the example SOAP messages have been replaced by hot text links to external files that contain the example. There is one file per example; c) The data model descriptions have been placed in their own section; d) Appendix A and B have been combined. The actual listing has been removed and hot text links are used to reference the listing.
Final Specification 1.0	11 June 2004	This is the formal Final Release of the IMS Person Management Services WSDL Binding specification.

Index

A

- Abstract Framework 5, 6
- API 6
- Attributes
 - Common
 - extension 13
 - recordInfo 11
 - sourcedId 15, 16, 17, 18, 19
 - userId 11
 - LangString
 - text 28
 - Person
 - dataSource 13
 - email 11
 - formatName 10
 - systemRole 11
 - Result
 - result 5
 - Role
 - status 16, 17, 18, 19, 20, 21, 22, 23
 - StatusInfo
 - description 5, 6, 10, 11, 12, 13, 14, 27
 - UserId
 - authentication 5
 - Values
 - list 19, 22, 23

B

- Binding technologies
 - SOAP 6, 8, 9, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 28
 - WSDL 5, 6, 8, 9, 25, 26, 27

C

- Classes
 - Group 5, 21
 - Description 5, 6, 27
 - Membership 5
 - Person 5, 6, 7, 8, 9, 15, 16, 17, 18, 19, 20, 21, 22, 25, 26, 27, 28
 - Name 15
- Common Services 5
- Conformance 5, 6

E

- Enterprise Service 5, 6, 7, 9, 27

G

- Group Management Service 5

M

- Membership Management Service 5
- Messages
 - Person

- changePersonIdentifierRequest 18, 19, 24
- changePersonIdentifierResponse 19, 24
- changePersonsIdentifierRequest 23, 24
- changePersonsIdentifierResponse 23, 24
- createByProxyPersonRequest 16, 24
- createByProxyPersonResponse 16, 24
- createByProxyPersonsRequest 20, 24
- createByProxyPersonsResponse 20, 24
- createPersonRequest 15, 24
- createPersonResponse 15, 16, 24
- createPersonsRequest 19, 24
- createPersonsResponse 19, 24
- deletePersonRequest 16, 24
- deletePersonResponse 17, 24
- deletePersonsRequest 20, 24
- deletePersonsResponse 20, 21, 24
- readPersonRequest 17, 24
- readPersonResponse 17, 24
- readPersonsForGroupRequest 21, 24
- readPersonsForGroupResponse 21, 22, 24
- readPersonsRequest 21, 24
- readPersonsResponse 21, 24
- replacePersonRequest 18, 24
- replacePersonResponse 18, 24
- replacePersonsRequest 22, 24
- replacePersonsResponse 23, 24
- updatePersonRequest 17, 24

- updatePersonResponse 18, 24
- updatePersonsRequest 22, 24
- updatePersonsResponse 22, 24

N

- Namespace prefix
 - esx 9
 - isb 9

O

- OCL 10, 11, 13
- Operations
 - Person
 - changePersonIdentifier 18, 19
 - changePersonsIdentifier 23
 - createByProxyPerson 16
 - createByProxyPersons 20
 - createPerson 15
 - createPersons 19
 - deletePerson 16, 17
 - deletePersons 20
 - readPerson 17
 - readPersons 21
 - readPersonsForGroup 21
 - replacePerson 18
 - replacePersons 23
 - updatePerson 17, 18
 - updatePersons 22

P

- Person Management Service 5, 6, 7, 8, 9, 25, 26, 27, 28

S

- Services
 - Group Management 5
 - Membership Management 5
 - Person Management 5, 6, 7, 8, 9, 25, 26, 27, 28
 - SOAP 6, 8, 9, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 28

W

- WSDL 5, 6, 8, 9, 25, 26, 27

IMS Global Learning Consortium, Inc. (“IMS”) is publishing the information contained in this IMS Person Management Services WSDL Binding (“Specification”) for purposes of scientific, experimental, and scholarly collaboration only.

IMS makes no warranty or representation regarding the accuracy or completeness of the Specification.

This material is provided on an “As Is” and “As Available” basis.

The Specification is at all times subject to change and revision without notice.

It is your sole responsibility to evaluate the usefulness, accuracy, and completeness of the Specification as it relates to you.

IMS would appreciate receiving your comments and suggestions.

Please contact IMS through our website at <http://www.imsglobal.org>

Please refer to Document Name: IMS Person Management Services WSDL Binding

Date: 11 June 2004